



Jazzy[®]

SELECT 14

The Jazzy Select[®] 14 Series delivers the advantages of patented mid-wheel drive for manoeuvring in tight, compact spaces. The Jazzy Select 14 is loaded with performance and convenience features like a powerful 60 amp controller, larger batteries for greater per-charge range, and an on-board battery charger.



Pride[®]
Mobility Products
Australia Pty. Ltd.
— LIVE YOUR BEST —

SPECIFICATIONS

Weight capacity	Up to 136 kg (300 lbs.)/XL: 181 kg (400 lbs.)
Maximum speed¹	Up to 7.24 km/h (4.5 mph)/XL: 6.5 km/h (4 mph)
Ground clearance	7.62 cm (3")
Turning radius²	53.34 cm (21")/XL: 37.82 cm (23.5")
Overall length²	96.52 cm (38")
Overall width²	62.865 cm (24.75")
Drive wheels	35.56 cm (14") solid or pneumatic, centre-mounted
Anti-tips	15.24 cm (6") solid, front-mounted
Castors	20.32 cm (8") solid, rear-articulating
Suspension	Limited
Drivetrain	Two-motor, mid-wheel drive
Braking system	Intelligent braking (electronic, regenerative disc brakes)
Standard electronics	60 amp controller
Standard seat	High-back
Specialty controls	N/A
Battery charger	Off-board, 5 amp
Per-charge range^{1,4}	Variable up to 16 km (10 miles)
Battery requirements⁵	(2) 12 volt deep-cycle
Battery size (largest)	(NF-22) 50-55 AH
Battery weight³	17.23 kg (38 lbs.) each
Base weight	47.63 kg (105 lbs.)/XL: 48.30 kg (106.5 lbs.)
Standard seat weight	19 kg (42.5 lbs.) (high-back)
Max. seating dimensions	46 cm x 51 cm (18" x 20")
Warranty	2-year limited

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

- 1) Range and speed vary with user weight, terrain type, battery charge, battery condition and tyre pressure. This specification can be subject to a variance of (+ 10% or - 5%) .
- 2) Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 3) Battery weight may vary based on manufacturer.
- 4) Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4, standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, -5%.
- 5) AGM or gel cell type required

FEATURES

- Patented mid-wheel drive design for tight space manoeuvrability
- 35.5 cm (14") knobby tyres and optimum weight distribution provide superior traction
- (NF-22) 50-55 AH batteries for maximum range
- 5 amp, off-board charger

OPTIONS

- High-back seat with solid seat pan
- Cup holder
- Weather cover
- Rear basket
- Oxygen tank holder
- Cane/crutch holder
- Walker holder

COLOUR



Jazzy Red